



brennenstuhl®



SICHERHEITSINFORMATIONEN

SAFETY INFORMATION

DE Sicherheitsinformationen	HU Biztonsági információk	LT Saugos informacija
EN Safety information	RU Информация о безопасности	LV Drošības informācija
FR Informations sur la sécurité	TR Güvenlik bilgileri	HR Sigurnosne informacije
NL Veiligheidsinformatie	FI Turvallisuustiedot	RO Informații privind siguranța
IT Informazioni sulla sicurezza	GR Πληροφορίες για την ασφάλεια	BG Информация за безопасност
SE Säkerhetsinformation	PT Informações de segurança	DK Oplysninger om sikkerhed
ES Información de seguridad	EE Ohutusalaane teave	NO Sikkerhetsinformasjon
PL Informacje dotyczące bezpieczeństwa	SK Bezpečnostné informácie	UA Інформація з техніки безпеки
CZ Bezpečnostní informace	SI Varnostne informacije	AR معلومات السلامة

WWW.BRENNENSTUHL.COM

04/11/2024

120mm

brennenstuhl®

EDL BLUPD30 0919 DE 3676
2 m H05VV-F 3G1,5
3680W MAX / 16A / 220-250V~
U_c=255 V~ 50Hz

L-N: $\overline{T3}$ U_{oc}=6,0 kV/U_p=2,0 kV
L/N-PE: $\overline{T3}$ U_{oc}=6,0 kV/U_p=2,0 kV

3676 XX23



Art. 1153580210
0484638/4323

USB input: 200-250V~ 50/60Hz 1A Max

USB output:

USB A port: 5.0V \equiv 3.0A MAX.15.0W,
9.0V \equiv 2.0A MAX.18.0W, 12.0V \equiv 1.5A MAX.18.0W

USB C port: 5.0V \equiv 3.0A MAX.15.0W,
9.0V \equiv 3.0A MAX.27.0W, 12.0V \equiv 2.5A MAX.30.0W,
15.0V \equiv 2.0A MAX.30.0W, 20.0V \equiv 1.5A MAX.30.0W

USB A+C port: 5.0V \equiv 4.8A MAX.24.0W total

5.0V \equiv 2.4A MAX.12.0W for each

η ₀=85,7% / η _{10%}=82,1% / P₀=0,21W

Hugo Brennenstuhl GmbH & Co.KG, Seestr.1-3, D-72074 Tübingen
lectra technik ag, Blegistrasse 13, CH-6340 Baar
service@brennenstuhl.com

Made in China

45mm

