

Schaltplan/ Wire diagram CONN. #1 A4+B4+A9+B9 A7 (D-) A6 (D+) A5 (CC) A1+B1+A12+B12 SHELL RED WHITE GREEN blue Ground wire CONN. #2 A4+B4+A9+B9 (VBUS) A7 (D-) A6 (D+) A5 (CC) A1+B1+A12+B12 (GND) SHELL				Artikel Nr. Item no.			Beschreibung Description						Länge Length (mm)							
				70192			DAT USB-C/C v2.0 0,5m textil ws PL						500±30							
				70193			DAT USB-C/C v2.0 1,0m textil ws PL						1000±30							
				70194			DAT USB-C/C v2.0 2,0m textil ws PL						2000±30							
				70195			DAT USB-C/C v2.0 3,0m textil ws PL						3000±30							
				36.0 6.65± 0.1 L 36.0 6.65± 0.1																
USB-C™ Supersoftes Textilkabel mit Metallsteckern - verstärkte Metallstecker mit Knickschutz sind auf über 10.000 Biegezyklen ausgelegt - bietet eine angenehme Haptik und ist schonend auf sensiblen Oberflächen Anschluss 1: Anschluss 2: Knickschutz: Kabelmantel - Material: Außenmantel - Material: Max. Strombelastbarkeit: Max. Leistung: Max. Übertragungsrate: USB-C™-Stecker USB-C™-Stecker beidseitig Silikon Textildgewebe 3 A 60 W 0,48 Gbit/s				USB-C™ Supersoft Textile Cable with Metal Plugs - reinforced metal plugs with kink protection are designed for over 10,000 bending cycles - has a pleasant feel and is gentle on sensitive surfaces Connection 1: Connection 2: Kink protection: Cable sheathing - material: Outer sheath - material: Current carrying capacity: Max. power: Max. data transmission rate: USB-C™-plug USB-C™-plug on both sides silicone textile fabric 3 A 60 W 0,48 Gbit/s																
				Änderungen				DAT USB-C/C v2.0 X,Xm textil ws PL										Blatt 1/1		
Datum 17.10.2024				Name alw		gez.: 10.10.2024		alw		gepr.: 10.10.2024		alw		Norm:		von				