

1	2	3	4	5	6	7	8	9	10	11	12	13	14		
A	PIN-Belegung / PIN Assignment														A
B	CN1 CN2 A1 A12 B1 B12 A4 A9 B4 B9 A2 A3 A5 A6 A7 A8 A10 A11 B2 B3 B5 B6 B7 B8 B10 B11 SHELL SHELL				CN1 2.40±0.03 6.65±0.2 24.0 6.4 8.25±0.03 12.8 40G/8K goobay 12.3 8.34^{+0.06}_{-0.02} 2.56±0.04 CN2										B
C															C
D															D
E															E
F	40G/8K 240W goobay				USB-C™-Adapter horizontal 90°, USB4™ - Sorgt für eine platzsparende Kabelführung - Hochwertiges, robustes Metallgehäuse - Kompatibel mit USB 3.1, USB 2.0, Thunderbolt™ 3 und Thunderbolt™ 4 Anschlüsse: Kontakte: Material Gehäuse: Max. Auflösung: Max. Datenübertragungsrate: Leistung: Isolationswiderstand: USB-C™-Buchse, USB-C™-Stecker PINs: vergoldet Innen: PVC 45P, schwarz Außen: Aluminiumlegierung 8K @ 60 Hz 40 Gbit/s Max. 240 W (48 V ; 5A) 300 V/10ms ---, ≥10 MΩ					USB-C™ Adapter Horizontal 90°, USB4™ - Ensures space-saving cable routing - High-quality, robust metal housing - Compatible with USB 3.1, USB 2.0 as well as Thunderbolt™ 3 and Thunderbolt™ 4 Connectors: Contacts: Material housing: Max. resolution: Max. data transmission rate: Power: Insulation resistance: USB-C™ socket USB-C™ plug nickel-plated PINs: gold plated Inside: PVC 45P, black Outside: Aluminium alloy 8K @ 60 Hz 40 Gbit/s Max. 240 W (48 V ; 5A) 300 V/10ms ---, ≥10 MΩ					F
G															G
H															H
I	Änderungen				Datum		Name		Bezeichnung				Blatt		I
J	Datum		Name		gez.:	25.07.2024	alw	USB-C 4.0 240W 40G 90°				goobay®		1/1	J
	28.08.2024		alw		gepr.:	25.07.2024	alw	Adapter Flach F-M							
					Norm:			Zeichnungs-Nr.:				von			
					Änderungen vorbehalten / Subject to change				74441						
1	2	3	4	5	6	7	8	9	10	11	12	13	14		