



Mini GaN Charger 20W / Mini GaN Charger 20W + USB-C® cable

PN: 32395, 32396

More power in less space. Verbatim's Mini GaN 20W USB-C Wall Charger (PN 32395) uses gallium nitride (GaN) technology to deliver efficient, cooler operation in a compact footprint. The USB-C port supports Power Delivery 3.0 with PPS and Quick Charge 3.0 for fast, reliable charging—up to 20W—across compatible phones, tablets, and everyday accessories.

Built-in safeguards (OCP/OVP/SCP/OTP) and a flame-resistant body add peace of mind for daily use and travel.

Also available as a bundle (PN 32396) with a USB-C to USB-C cable (1 m) rated to 60W with 480 Mbps data speed.

- **GaN efficiency in a mini size** — Integrated GaN technology delivers efficient charging with less heat in a compact, travel-friendly design.
- **Up to 20W fast charging** — USB-C supports PD 3.0 with PPS and QC 3.0 for stable, rapid power delivery to compatible phones, tablets, and accessories.
- **Safety you can trust** — Built-in protection against over-current, over-voltage, short-circuit, and over-temperature, plus a flame-resistant enclosure.
- **USB-C compatibility** — Works with USB-C devices including smartphones, tablets, power banks, and accessories.
- **Charge & sync bundle (PN 32396)** — Includes a USB-C to USB-C cable (1 m) rated 60W with USB 2.0 480 Mbps data speeds—ideal at home, office, or on the go.

Notes: Fast-charging performance depends on device and charger protocol support (PD/PPS/QC). 20W output is not intended for powering high-wattage laptops.




PD 3.0 20W



Compact Design



PD 3.0 20W



Compact Design



USB-C Cable
Included



Mini GaN Charger 20W / Mini GaN Charger 20W + USB-C® cable



PN: 32395, 32396

Product Specifications

Charger:

- Input: 180-240 V AC 50/60 Hz 0.7 A (max.)
- Output: USB-C PD 3.0: 5 V = 3 A, 9 V = 2.22 A, 12 V = 1.67 A (20 W max.)
- Safety Protection: Short circuit / Over current / Over temperature / Over charge voltage /

USB Cable (only for 32396):

- USB-C to C
- up to 60 W charging, Supports PD 3.0
- up to 480 Mbps data transfer
- Length: 100 cm
- Operating Temperature: 0°C ~ +25 °C
- Storage Temperature: -25 °C ~ +40 °C
- Operating Humidity: 20%-80%
- Certificates: CE, EAC, RoHS
- **Indoor use only!**

Pack Content

- Verbatim Mini GaN Charger 20W US plug White
- USB-C to USB-C cable 1 m (Only 32396)
- Quick Start Guide



PN	# Devices	USB-C	Max Total Output	Power Delivery	Q.C.	Cable	Charging Power	Data Transfer
32395	1	1 x Max. 20W	20W	PD 3.0	3.0	-	-	-
32396	1	1 x Max. 20W	20W	PD 3.0	3.0	USB-C to C	Up to 60W	480 Mbps

Languages

Front of pack: English

Back of pack: English, French, German, Dutch, Italian, Spanish, Portuguese, Polish, Russian, Czech, Hungarian, Greek, Serbian, Croatian, Slovakian, Romanian, Turkish, Traditional Chinese, Simplified Chinese, Korean, Japanese

Quick Installation Languages

English + Technical support text in English, French, German, Dutch, Italian, Spanish, Portuguese, Polish, Russian, Czech, Hungarian, Greek, Serbian, Croatian, Slovakian, Romanian, Turkish, Traditional Chinese, Simplified Chinese, Korean, Japanese

Mini GaN Charger 20W / Mini GaN Charger 20W + USB-C® cable



Reorder No.	Description	Tariff Code	Barcode	EAN-128	EAN-14
32395	Verbatim Mini GaN Charger 20W EU	85044060	023942323952	(02)00023942323952(37)40(91)864 (02)00023942323952(37)0160(91)864	20023942323956 50023942323957
32396	Mini GaN Charger 20W bundle with USB-C cable (EU)	85044060	023942323969	(02)00023942323969(37)40(91)864 (02)00023942323969(37)0160(91)864	2002394233963 5002394233964

Reorder No.	32395	32396
Product Dimensions L x W x H	35.8 x 30.2 x 67.2 mm	Charger: 35.8 x 30.2 x 67.2 mm Cable: 1000 mm
Product Weight	36	53 (36+17) g
Units per Pack	1	1pcs each
Pack Dimensions L x W x H	60 x 33 x 94 (116.5 with Hanger) mm	80 x 33.5 x 94 (116.5 with Hanger) mm
Pack Weight	60 g	82 g
Packs per Inner Carton (MOQ)	40	40
Inner Carton Dimensions L x W x H	370 x 200 x 140 mm	380 x 210 x 175 mm
Inner Carton Weight	2527 g	3405 g
Packs per Outer Carton	160	160
Outer Carton Dimensions L x W x H	395 x 425 x 310 mm	430 x 395 x 380 mm
Outer Cartons Weight	10900 g	14636 g
Outer Cartons per Layer	8	6
Layers per Pallet	3	2
Packs per Pallet	3840	1920

