

Product Data Sheet

GP LD CLS60 8.6-60W E27 W FR

Order code	EAN	Packaging - SKU	
777954-LDCE1	4895149777954	Eco blister, 1 pc/SKU	
087687-LDB3	4895149087687	Colour gift box, 3 pc/SKU	
Product			
Category		LED Lamps	
Series		CLASSIC - FROSTED	
Model		CLASSIC FROSTED	
Description		GP LD CLS60 E27 8.6-60W 220-240V FR	GP
General descriptio	n		
Energy label		F	
Lamp shape		Classic A60	
Lamp base		E27	
Dimmable		No	
Mercury free		Yes	41331-0
Mercury content		0.0 mg	
Recycling		Yes	
1.coyomiy		100	109
Electrical characteristics			100
Nominal wattage 8.6 W ±10%			
Rated wattage		8.6 W	
Equivalent incandescent lamp power		60 W	
Power factor		>0.5	Spectral Distribution
Voltage		220-240 V	1.21
Operating frequency		50/60Hz	
Lamp current		59 mA	1.0
Weighted Energy Consumption		9 KWh / 1000 h	0.8-
3 37			59-0 C C C C C C C C C C C C C C C C C C C
Light technical characteristics			ο. 4 :
Light colour		WARM WHITE	
Colour temperature		2700 K ±270K	0.2-
Colour rendering index (Ra)		≥80	0.0380 500 600 700 800
Colour consistency		<6 SDCM	Wavelength (nm)
Nominal luminous flux		806 lm ±10%	
Rated luminous flux		806 lm	GP LED Lamps are designed for
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5s s	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	Instant start with full light output
Product dimensions			Available in most common lamp bases
Product dimensions		400	for household use
Overall length (L)		109 mm ±1 mm	• No UV
Diameter (D)		60 mm ±1 mm	Applications
Product Compliance		CE EBB BOHS BEYON	Applications • Domestic and commercial applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications Constal illumination
Warranty 12 months from ex-factory date			General illumination
* Please refer to website www.gp-lighting.com for the list of compatible dimmers.			Can be used everywhere at home
			Use outdoors only in enclosed and
			ventilated luminaires

www.gp-lighting.com